



**NOTES:**

1. STOP/STREET NAME SIGN SHOWN FOR EXHIBIT PURPOSES, DETAIL SHALL APPLY TO ALL CARY-MAINTAINED, GROUND-MOUNTED TRAFFIC SIGNS.
2. FOR 12-INCH STREET NAMES SIGNS, A 2-INCH SQUARE POST WITH ANCHOR SLEEVE SHALL BE PROVIDED IN LIEU OF 3 LB U-CHANNEL.
3. CONCRETE MIX SHALL BE 50 LB (APPROX. 0.375 CU FT) SACK OF PRE-BLENDED MIXTURE OF CEMENT AND AGGREGATES DESIGNATED "HIGH STRENGTH" FOR GENERAL STRUCTURAL USE AND REQUIRING ONLY THE ADDITION OF WATER.
4. COMPACT DISTURBED AREAS ABOVE CONCRETE COLLAR IN MAXIMUM 6-INCH LIFTS.
5. U-CHANNEL POSTS THAT ARE MECHANICALLY DRIVEN A MINIMUM OF 24-INCHES INTO UNDISTURBED GROUND MAY OMIT THE CONCRETE COLLAR.
6. SIGN MATERIAL SHALL BE MINIMUM 0.125" ALUMINUM WITH RETROREFLECTIVE SHEETING THAT MEETS ASTM D4956 AND IS LISTED ON THE NCDOT APL.

**STANDARD GROUND MOUNTED TRAFFIC SIGN**

DETAIL No.

3600.08



EFFECTIVE:07/01/23