

TYPICAL SECTION

5'-0" MIN.

PLAN VIEW

ROADWAY

BACK OF CURB

-R/W

LIGHT POLE

TRAIL

STREETSCAPE BUFFER

MIN. 50-FT RADIUS

10'-0" TRAIL


MINIMUM 5'-0" BETWEEN TRAIL AND PLANTINGS (SEE ADDITIONAL NOTES ON LANDSCAPING SHEETS)

20-FT 10C GREENWAY EASEMENT

40'-0" MAXIMUM

NOTES:

1. NO ABOVE GROUND UTILITIES OR UTILITY SURFACE COVERS/PLATES/MANHOLES SHALL BE LOCATED WITHIN TRAIL AND SHALL BE MINIMUM 2 FEET FROM THE EDGE OF TRAIL.
2. TRAILS WILL MEANDER BUT SHALL BE LOCATED MINIMUM 5 FEET FROM THE BACK OF CURB.
3. SIDE SLOPES SHALL NOT EXCEED 3:1. CUT & FILL SLOPES SHALL TIE INTO EXISTING SLOPES TO CREATE AN EVEN TRANSITION.



STANDARD ASPHALT STREET-SIDE TRAIL

DETAIL No.

9100.04

EFFECTIVE:07/01/23