

PLAN VIEW
(FOR ELEVATION VIEW
SEE DETAIL 9500.08)

SECTION A-A

NOTE:
TO BE USED ONLY ON A
CASE-BY-CASE BASIS AS
APPROVED BY THE CARY
TRANSPORTATION DEPARTMENT.

8"x 8" MINIMUM PILING TO BE
DRIVEN OR AUGERED. BACKFILL
HOLE WITH LEAN CONCRETE
AFTER PILE INSERTION (TYP.)


COMPOSITE MATERIAL INFORMATION

(OPTIONAL FOR HANDRAIL AND
DECKING SURFACE)

MFG: MOISTURE SHIELD
www.moistureshield.com
**OR EQUIVALENT WITH APPROVAL
BY CARY TRANSPORTATION STAFF**
PRODUCT: MOISTURESHIELD VANTAGE
COLOR: CAPE COD GREY

NOTE:

THESE ARE PREFERRED DESIGN ELEMENTS.
SEPARATE SIGNED AND SEALED
STRUCTURAL DESIGNS OF BOARDWALK ARE
TO BE SUBMITTED AND APPROVED PRIOR
TO CONSTRUCTION. FINAL ENGINEERING
DRAWINGS INCLUDING FOUNDATIONS MUST
BE SUBMITTED FOR APPROVAL.



EFFECTIVE:07/01/23

5,000 LB BOARDWALK (PLAN & SECTION VIEW)

DETAIL No.

9500.07