

CAUTION
NONPOTABLE WATER
DO NOT DRINK

- NOTES:**
1. HOSE BIB SHALL ACCOMMODATE STANDARD 3/4 INCH GARDEN HOSE.
 2. ALL FITTINGS SHALL BE 'NO LEAD' BRASS MEETING UNS C89833 AS PER ASTM B584.
 3. SIGN SHALL BE 21"x15" & 0.125 MINIMUM GAUGE ALUMINUM GRADE 6061 OR BETTER. LETTERING SHALL BE 1-3/4 INCH.
 4. RPZ MAY BE OMITTED IN SOME APPLICATIONS OF NONPOTABLE USE WHERE THE HYDRANT IS SEPARATELY METERED AND ALL PLUMBING CODE REQUIREMENTS ARE MET.

SIPHON BREAK

18" MINIMUM
30" MAXIMUM

FINISHED GRADE

24" MIN. DEPTH

CONCRETE

RPZ PER DETAIL 6200.02

4" x 24" x 24"
CONCRETE
SPLASH PAD


1 CUBIC FOOT OF
#57 WASHED STONE

12"

12"

METER

TYPE K, 1" DIAMETER COPPER
TUBING WITH THREADED TO
COMPRESSION FITTING AT HYDRANT



EFFECTIVE: 07/01/24

STANDARD YARD HYDRANT (NON-FREEZE)

DETAIL No.

6000.26