

**NOTES:**


1. EITHER SOLID BRICK, SOLID BLOCK, OR PRECAST CONCRETE MAY BE USED.
2. FOR 24 INCH RCP AND LARGER USE PIPE DIAMETER PLUS 12 INCHES FOR MINIMUM INSIDE DIMENSION.
3. GRATED INLETS SHALL NOT BE USED WITHIN TRAVEL AREAS.
4. ONLY TOP AND BOTTOM STEPS REQUIRED ON BOXES INSTALLED IN THE PUBLIC RIGHT-OF-WAY.
5. YARD INLETS DEEPER THAN 10 FEET SHALL REQUIRE DOUBLE WALLS.
6. PRECAST REINFORCED CONCRETE SLAB MAY BE USED AS TOP WITH GRATE OPENING CAST IN SLAB.
7. SLAB THICKNESS AND REINFORCEMENT FOR SOIL AND TRAFFIC LOADING TO BE DESIGNED BY AN ENGINEER.
8. PLACE SAND BAG FILLED WITH #57 STONE OVER WEEP HOLE ON BOX EXTERIOR DURING CONSTRUCTION.

NTS

**STANDARD YARD INLET WITH GRATE AND FRAME**

DETAIL No.

8000.02



EFFECTIVE: 07/01/24