



- NOTES:**
- GREENWAY TRAIL SHALL BE CONSTRUCTED AT WIDTH INDICATED ON SITE LAYOUT & GRADING SHEETS.**
  - TRAILS GREATER THAN 10 FEET WIDE SHALL HAVE 2 FOOT WIDE SHOULDERS, UNLESS SPECIFIED OTHERWISE ON THE SITE LAYOUT & GRADING SHEETS.
  - CONTRACTOR IS RESPONSIBLE FOR RE-ESTABLISHING ALL SLOPES DISTURBED BY CONSTRUCTION.
  - NO ABOVE GROUND UTILITIES OR UTILITY SURFACE COVERS/PLATES/MANHOLES SHALL BE LOCATED WITHIN TRAIL AND SHALL BE MINIMUM 2 FEET FROM THE EDGE OF TRAIL. RAISED MANHOLES SHALL BE MINIMUM 4 FEET FROM TRAIL EDGE.
  - ALL TRAILS SHALL BE LOCATED MINIMUM 5 FEET FROM THE BACK OF CURB.
  - SIDE SLOPES SHALL NOT EXCEED 3:1. CUT & FILL SLOPES SHALL TIE INTO EXISTING SLOPES TO CREATE AN EVEN TRANSITION.
  - CROSS SLOPE TYPICALLY TO LOW SIDE BUT CROSS SLOPE TO INSIDE OF DOWNHILL CURVES, WITH GRADUAL TRANSITIONS BETWEEN ANY CROSS SLOPE DIRECTION CHANGES.



EFFECTIVE:07/01/24

## STANDARD ASPHALT GREENWAY TRAIL

DETAIL No.

9100.01