Facility Name: Holly Brook PS **Inspection Date:** 9/8/2011 **ID Number:** 024 **Pump Drawdown:** 2/8/2011

Pump One Condition: Good

Type: Submersible Pump One: 131 gpm Discharge Diameter: 6" Pump Two: 193 gpm Control: Float / FVNR Starter Firm Capcity: 131 gpm 171 Motor Horsepower: 25 Design Point (flow): gpm

Pump RPM: 1750 Design Point (pressure): 117 feet of water

Manufacturer: Myers Rep: Pentair Pump Group

Model: 4VC 704-504-3111

419-289-1144

Wetwell: 8' Diameter 6.33' Deep Vol: 2,400 gal

Pump Two

Type: Submersible Discharge Diameter: 6"

Control: Float / FVNR Starter

Motor Horsepower: 25 Pump RPM: 1750

Manufacturer: Fairbanks Morse Rep: HD Supply Model: 5433MV 828-324-9705

913-371-5000

Grinder: None Trash basket

Comments:


- -trash basket, no grinder
- -temporary generator
- -8' diameter wetwell; coating in fair conditoin
- -pump guide top supports corroded (not significantly)
- -aluminum trash rack and guide and hatches at wetwell are in good condition
- -10'x8' valve vault damp inside some ground water
- -aluminum hatch and coating on valve vault in good condition
- -odor control, Odophos, and two metering pumps inside precast building not currently in use
- -has carbon adsorption odor system
- -modular precast building and containment wall inside building in good condition
- -exterior slab on grade showing signs of settling and cracking
- -expansion joint between slab and pump station/valve vault has no sealant and has vegetation growing in it




Holly Brook PS Pump 1 Pump Curve

Pump Performance






Holly Brook PS Pump 2 Pump Curve





Holly Brook Pump Station



Control Panel



Portable Generator



Valve Vault



Wetwell







Odor Contraol



Chemical Building



Chemical Building



Chemical Building



Eye Wash



Basket

